

## **Topdresser 1800**

An 18 cubic foot (509 cubic liters), bed-mounted topdresser that is durable, flexible and delivers an even rate of application – whether a light or heavy topdressing application is desired.



	TOPDRESSER 1800, MODEL 44225*			
HOPPER CAPACITY	18 cu. ft. (509 liter) or 1,476 lbs. (669.5 kg)			
SPREADING WIDTH	60" (152 cm)			
TOPDRESSING SPEED	Up to 8 mph (12.8 km/h).			
TRANSPORT SPEED	Up to 12 mph (19.3 km/h).			
CONVEYOR BELT	Seamless 60" (152.4 cm) wide belt, polyester mono-filament interwoven material w/vulcanlized PVC "v-pattern" traction surface.			
METERING GATE	Infinitely variable from closed to 3.5" (8.9 cm) opening for light to heavy applications. Flexible edge and spring release.			
CONTROLS	Hydraulic engage/disengage lever from operators console.			
DRIVE	Remote hydraulic from utility vehicle.			
DIMENSIONS /WEIGHT	<b>Height</b> 43" (109 cm)	<b>Length</b> 52" (132 cm)	<b>Width</b> 72.5" (184 cm)	Shipping Weight 893 lbs. (405 kg)
WARRANTY	Two-year limited warranty. Refer to operator's manual for further details.			

<sup>\*</sup>Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.



